

# DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS D206-642 REV. P  
AND INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D206-642 REV.5

REF. FAA STC: SA00475SE

REF. CANADIAN STC: SH98-4

REF. EASA STC: EASA.IM.R.S.01320

The purpose of this Dart Service Instruction is to clarify the compatibility section of IIN-D206-642 and ICA-D206-642. Update the Crosstube Compatibility section as follows:




## CROSSTUBE COMPATIBILITY

The Dart skidtube installations are approved replacements for skidtube and saddles on the 206 A/B and 206L/407 series Rotorcraft when installed with the cross tubes listed in the following table or approved compatible replacement crosstubes.

AIRCRAFT MODELS	DART INSTALLATION	FORWARD CROSSTUBES	AFT CROSSTUBES
206A/B w/ Low Gear	D206-642-111 D206-642-112 D206-642-113 D206-642-114	206-050-119-001 or 206-050-119-005 or 206-050-119-103 or 206-050-286-101 or 206-320-101 or 206-320-119 or 206-320-121	206-050-119-003 or 206-050-119-007 or 206-050-119-101 or 206-050-286-103/-105 or 206-320-102 or 206-320-120 or 206-320-122/-126
206A/B w/ High Gear	D206-642-211 D206-642-212 D206-642-215 D206-642-216 D206-642-611 D206-642-612	206-050-107-025 or 206-050-107-119 or 206-050-288-101 or 206-321-019 or D206-667-101	206-050-107-027 or 206-050-107-121 or 206-321-022 or D206-667-201
206A/B w/ High Gear Thru Bolt	D206-642-213 D206-642-214 D206-642-217 D206-642-218 D206-642-613 D206-642-614	206-050-107-025 or 206-050-107-119 or 206-050-288-101 or 206-321-019 or D206-667-101	206-050-288-103 or 206-321-024 or D206-667-201
206L/L-1/L-3/L-4 w/ Low Gear 407 w/ Low Gear	D206-642-311 D206-642-312 D206-642-313 D206-642-314	206-053-119-003 or 206-053-119-103 or 206-053-119-107 or 206-053-201-101 or 407-050-101-101 or 206-325-119 or 407-722-101	206-053-119-001 or 206-053-119-101 or 206-053-119-105 or 206-053-201-103 or 407-050-102-101 or 206-325-120 or 407-723-104
206L/L-1/L-3/L-4 w/ High Gear	D206-642-311/-312 D206-642-313/-314 D206-642-411/-412 D206-642-413/-414 D206-642-511/-512 D206-642-513/-514 D206-642-515/-516 D206-642-517/-518	or 206-053-109-007 or 206-053-109-103 or 206-053-109-105 or 206-053-109-109 or 206-053-203-101 or 206-323-021 or D206-667-103	or 206-053-109-005 or 206-053-109-101 or 206-053-109-107 or 206-053-203-103 or 206-323-022 or D206-667-203
407 w/ High Gear	D206-642-311/-312 D206-642-313/-314 D206-642-511/-512 D206-642-513/-514 D206-642-515/-516 D206-642-517/-518	407-050-201-101 or 407-724-101 or D407-667-105	407-050-202-101 or 407-725-104 or D407-667-205

The Dart D206-642-111/-112/-113/-114/-213/-214/-217/-218/-613/-614 skidtubes are compatible with BHT STC SR09397RC for internal gross weight increase from 3200 lbs to 3350 lbs as described in BHT-206-SI-129.

The Dart D206-642-211/-212/-215/-216/-611/-612 skidtubes are also compatible with BHT STC SR09397RC as long as they are installed with Dart D206-667-101/-201 crosstubes per Canadian STC SH01-5 (ref. FAA STC SR01304NY).

A	NEW ISSUE	AJS	13.05.07
REV.	DESCRIPTION	BY	DATE
DESIGN	AJS	<b>DART AEROSPACE USA, INC</b> KENT, WA	
DRAWN	AJS		
CHECKED		DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9655	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		PAPERWORK CLARIFICATION	NTS
DATE	13.05.07	<small>COPYRIGHT © 2013 BY DART AEROSPACE USA, INC THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.</small>	